LARSON

Installation Tool Checklist

Before you leave the store, make sure you have all the tools and materials you need to complete the installation.

Applicable Models

- 150 Maximum View
- Larson 60 MT Maximum View
- Lakeview Maximum View

Two People Required

- ☐ **#2 PHILLIPS HEAD BIT**



- ☐ **1/8" DRILL BIT**



- ☐ **3/32" DRILL BIT**



- ☐ **#2 PHILLIPS HEAD SCREWDRIVER**



- ☐ **CAULK GUN & SEALANT**
  Larson recommends selecting a high-quality hybrid polymer, elastomeric or polyurethane sealant.



- ☐ **CUT-RESISTANT GLOVES**



- ☐ **FLAT HEAD SCREWDRIVER**



- ☐ **8" LEVEL**



- ☐ **NEEDLE NOSE PLIERS**



- ☐ **PENCIL**



- ☐ **POWER DRILL & IMPACT DRIVER**
  A second drill or impact driver is recommended to save time.



- ☐ **SAFETY GLASSES**



- ☐ **SAWHORSES**



- ☐ **SCISSORS**



- ☐ **SOAPY WATER**



- ☐ **STEP LADDER**



- ☐ **TAPE**



- ☐ **TAPE MEASURE**



©2025 Larson Manufacturing Company, LLC. All rights reserved.